

SPECIFICATION SHEET: WEATHERWOOD VARNISH TOPCOATS

W▲W
WEATHERWOOD▲STAINS

Architectural Wood Products

• VINTAGE WOOD, WITHOUT THE HUNDRED YEAR



MSRP WOOD STAINS:

- ▲ Quart @ \$79
- ▲ Gallon @ \$300

MSRP VARNISH:

- ▲ Quart @ \$40
- ▲ Gallon @ \$120
- ▲ 5 Gallon @ \$1500

MSRP POLYURETHANE:

- ▲ Quart @ \$50
- ▲ Gallon @ \$150

MSRP MAINTENANCE OILS:

- ▲ ½ Pint @ \$40
- ▲ Quart @ \$120

MSRP EXTER. WATERPROOFER:

- Quart @ \$32
- Gallon @ \$95

WEATHERWOOD VARNISHES

WW Varnish topcoats are architectural quality specially formulated for their compatibility with Weatherwood reactive, wood stains. Varnishes come in three sheens. The less the sheen, more it will look like the original Weatherwood stained wood. For example, Dead Flat will have almost no visible difference, while Satin is just barely noticeable.

Varnish MSDS available on WW website. 1 Gallon = 400 sq/ft.

WW Varnishes are:

- ▲ Architectural Quality
- ▲ Commercial & Residential
- ▲ Non-Yellowing
- ▲ VOC Compliant
- ▲ Water-Based
- ▲ Interior

USE:

For furniture, cabinetry, millwork, doors, wainscoting, paneling, etc.

WWW.WEATHERWOODSTAINS.COM



DIRECTIONS:

PREP: After applying Weatherwood Stains reactive wood stain, allow to dry. Sanding with 120-220 optional.

APPLICATION: Use sprayer or brush. **BRUSH:** Use quality brush. On large projects, work in sections, keeping a wet edge. **SPRAY:** Thin product 15-20% before using. Fill a gravity sprayer and apply in up to three coats. Apply with broad strokes in overlapping streams. Drying varnish may look blue/purple and that's normal. It will dry clear. Allow to dry between coats. Up to three coats allowed.

DRYING: Dry time 20-60 min. Allow for longer dry times in damp / humid climates.

See website for additional images, product safety & warranty info.

