

SPECIFICATION SHEET: WEATHERWOOD MAINTENANCE OIL TOPCOATS

W.W

WEATHERWOOD ▲ STAINS

WOOD STAIN

▲ VINTAGE WOOD, WITHOUT THE HUNDRED YEAR WAIT ▲

Quality Architectural Wood Products



WW MAINTENANCE OILS

MSRP STAIN PRICING:

- ▲ 1 QUART @ \$79
- ▲ 1 GALLON @ \$300
- ▲ 5 GALLONS @ \$1500



MSRP MAINTENANCE OIL PRICING:

- ▲ 1/2 PINT @ \$40
- ▲ 1 QUART @ \$120



MSRP VARNISH PRICING

- ▲ 1 QUART @ \$40
- ▲ 1 GALLON @ \$120



ORDERING INFO:

MON-FRI 9-6 PST

P: (801) 623-2609 | F: (801) 893-0831

WWW.WEATHERWOODSTAINS.COM

WEATHERWOOD VARNISH PRODUCT FACTS:

WW Maintenance Oil topcoats are architectural quality specially formulated to accentuate the Weatherwood reactive, wood stains' colors. Maintenance Oils come in two colors, white and clear.

WHITE: Used to maintain the color of lightly colored stained woods or to lighten dark colored woods. **CLEAR:** Used to bring out the rustic look of dark colored woods. Maintenance Oil MSDS available on WW website. 1 Quart = 750 sq/ft.

WW Varnishes are:

- ▲ Architectural Quality
- ▲ Stain Resistant
- ▲ Oil-Based
- ▲ Commercial & Residential
- ▲ Moisturizes Wood
- ▲ Low VOC

USE:

For flooring, furniture, cabinetry, millwork, doors, wainscoting, paneling, etc.



DIRECTIONS:

PREP: Apply as a topcoat Weatherwood Stains reactive wood stain. Allow stains are dry, sanding with 120-220 optional.

APPLICATION: Use cloth or brush to apply. Apply one very light coat of oil, using one brush/cloth to apply oil and a second clean cloth to buff product back off. Apply up to three coats based on look and desired protection.

DRYING: Maintenance Oil should cure 24-48 hours. Proper air flow and warm conditions aid dry time. Allow longer for damp/humid climates.

CARE: Apply maintenance oil yearly to keep the hard-wax look.

* Optional step, allow maint. oil to cure full dry time. Apply an additional topcoat, like poly, lacquer, varnish. to seal in look.

