

SPECIFICATION SHEET: WEATHERWOOD POLYURETHANE

W▲W

WEATHERWOOD▲STAINS

Architectural Wood Products

• VINTAGE WOOD, WITHOUT THE HUNDRED YEAR WAIT •



MSRP WOOD STAINS:

- ▲ Quart @ \$79
- ▲ Gallon @ \$300

MSRP VARNISH:

- ▲ Quart @ \$40
- ▲ Gallon @ \$120

MSRP POLYURETHANE:

- ▲ Quart @ \$50
- ▲ Gallon @ \$150
- ▲ 5 Gallon @ \$750

MSRP MAINTENANCE OILS:

- ▲ ½ Pint @ \$40
- ▲ Quart @ \$120

MSRP EXTER. WATERPROOFER:

- ▲ Quart @ \$32
- ▲ Gallon @ \$95

WEATHERWOOD POLYURETHANE

OVERVIEW:

WW Polyurethane topcoats are architectural quality and specially formulated for their compatibility with Weatherwood reactive, wood stains. This is our toughest level of protection for your hardest to protect spaces, like hardwood floors. Polyurethane come in a satin sheen.

MSDS available on website. 1 Gallon = 400 sq. ft.

WW is:

- ▲ Architectural Quality
- ▲ Commercial & Residential
- ▲ Non-Yellowing
- ▲ VOC Compliant

USE:

Especially formulated for hardwood floors, but suitable for cabinetry, millwork, doors, wainscoting, etc.

WWW.WEATHERWOODSTAINS.COM



DIRECTIONS:

PREP: To apply over Weatherwood Stains' reactive wood stains, allow to thoroughly dry. Finish sand with 220-320 optional depending on grain.

For raw wood, prep wood by first sanding with 120 grit, then 220 or 320.

APPLICATION: Apply polyurethane using a squeegee, quality bristle brush, or spray gun.

BY HAND: Use quality brush for small projects. Use a squeegee on large projects, work in sections, keeping a wet edge. Up to 3 coats allowed.

SPRAY: Thin product 10-15% before using. Fill a gravity sprayer and apply with broad strokes in overlapping streams. Polyurethane will dry crystal clear with satin sheen. Up to 3 coats allowed

DRYING: Dry time 20-60 min. Allow for longer dry times in damp / humid climates. Allow to dry up to 4 hrs., or more than 24 hrs. between coats.

