

W.W

WEATHERWOOD ▲ STAINS

WOOD STAIN

▲ VINTAGE WOOD, WITHOUT THE HUNDRED YEAR WAIT ▲

VOC Free | Non-Toxic | Water-Based
EXTERIOR & INTERIOR



WEATHERWOOD VARNISHES

MSRP STAIN PRICING:

- ▲ 1 QUART @ \$79
- ▲ 1 GALLON @ \$300
- ▲ 5 GALLONS @ \$1500



MSRP MAINTENANCE OIL PRICING:

- ▲ 1/2 PINT @ \$40
- ▲ 1 QUART @ \$120



MSRP VARNISH PRICING

- ▲ 1 QUART @ \$40
- ▲ 1 GALLON @ \$120



ORDERING INFO:

MON-FRI 9-6 PST

P: (801) 623-2609 | F: (801) 893-0831

WWW.WEATHERWOODSTAINS.COM

WEATHERWOOD VARNISH PRODUCT FACTS:

WW Varnish topcoats are architectural quality specially formulated for their compatibility with Weatherwood reactive, wood stains. Varnishes come in three sheens. The lesser the sheen, more it will look like the original Weatherwood stained wood. For example, Dead Flat will have almost no visible difference, while Satin is just barely noticeable, and Super Gloss will darken a shade or more. Varnish MSDS available on WW website. 1 Gallon = 400 sq/ft.

WW Varnishes are:

- ▲ Architectural Quality
- ▲ Non-Yellowing
- ▲ Water-Based
- ▲ Commercial & Residential
- ▲ VOC Compliant
- ▲ Interior

USE:

For furniture, cabinetry, millwork, doors, wainscoting, paneling, etc.



DIRECTIONS:

PREP: After applying Weatherwood Stains reactive wood stain, allow to dry. Sanding with 120-220 optional.

APPLICATION: Use sprayer or brush. **BRUSH:** Use quality brush. On large projects, work in sections, keeping a wet edge. **SPRAY:** Thin product 15-20% before using. Fill a gravity sprayer and apply in up to three coats. Apply with broad strokes in overlapping streams. Drying varnish may look blue/purple and that's normal. It will dry clear. Allow to dry between coats. Up to three coats allowed.

DRYING: Dry time 20-60 min. Allow for longer dry times in damp / humid climates.

See website for additional images, product safety & warranty info.

